



www.greatwallcrusher.com

 **Spiral Screen**
螺旋筛

Usage and Application

SL-U2 series of spiral screen is mainly used in industry of coal dressing, electricity generation, cement, oil refining, fertilizer, etc. Its function is to screen and separate dry&wet coal, not only to have good performance in screening dry material, but also to avoid sieve hole blocked in screening wet material especially fine size with moisture. It has high rate of screening which is new equipment in sieving wet, stick, fine coal.

Features

- 1.High rate for through screen;
- 2.Wet stick coal will not block screen hole;
- 3.No vibration, low noise;
- 4.Fast moving speed,big capacity(2 times bigger than vibrating screen);
- 5.Sieve surface is sturdy and durable;
- 6.No new crushing;
- 7.When used in electricity station, full closed product can protect better environment of coal production system ;

主要技术参数 / Main Specifications

Item	Standard series	Area (M2)	Capacity (t/h)	Efficiency (%)	Feeding Size (mm)	Feeding Moisture (%)	Inclination angle of screen (Degree)	Units (pcs)	Dimension L×W×H (m)	Weight (t)	Motor Power (kW)
1	SL-U2100/2.5-C	15	≤2000	90	0~500	NoLimitation	0	4	7.6×3.5×3	24.4	11×8
2	SL-U2100/2.5-B	11.25	≤1600	90				3	5.8×3.5×2.3	18.3	11×6
3	SL-U2100/2-B	9	≤1200	90				3	5.8×3×2.3	16.8	7.5×6
4	SL-U2100/2-A	6	≤800	85				2	4×3×1.6	11.2	7.5×4
5	SL-U2100/1.5-B	6.75	≤700	90				3	5.8×2.5×2.3	14.4	5.5×6
6	SL-U2100/1.5-A	4.5	≤500	85				2	4×2.5×1.6	9.6	5.5×4

注：技术数据如有变动，恕不另行通知。
Note: Any change of technical data will not inform additionally.



Zhengzhou Great Wall Heavy Industry Machinery Co., Ltd.

Add: No. 15, Longjiang Road, Shangjie District, Zhengzhou City, China.
Tel: 0086-371-63769782 Fax: 0086-371-63769781 Post Code: 450044
http://www.greatwallcrusher.com E-mail: sales@greatwallcrusher.com